

WHAT IS CLAIMED IS:

1. ~~A method in a device having a display, the method comprising:~~

generating at least one sensor signal using
at least one sensor in the device;

generating one or more context values that
indicate how the device is situated
relative to one or more objects based
on the at least one sensor; and

a control step for using a context value to
control the operation of one or more
aspects of the device.

2. The method of claim 1 wherein generating
one or more context values comprises generating a
tilt context value that indicates how the device is
tilted relative to the earth.

3. The method of claim 2 wherein the control
step for using a context value to control the
operation of one or more aspects of the device
comprises changing the orientation of an image on the
display based on the tilt context value.

4. The method of claim 3 wherein the control
step for using a context value to control the
operation of one or more aspects of the device
further comprises changing the mapping of directional
inputs relative to the display.

Sub
all

09875477-060601

5. The method of claim 3 wherein generating a context value further comprises generating a flat context value that indicates that the device is laying flat and wherein the control step for using a context value to control the operation of one or more aspects of the device further comprises selecting an orientation for an image on the display by finding a tilt context value that was maintained for longer than a set period of time before the flat context value was generated.

6. The method of claim 2 wherein the step for using a context value to control the operation of one or more aspects of the device comprises changing the contrast level on a display based on the tilt context value.

7. The method of claim 2 wherein the step for using a context value to control the operation of one or more aspects of the device comprises scrolling an image on the display based on the tilt context value, the rate of scrolling being based on the difference between a current tilt context value and an initial tilt context value that was determined when scrolling was initiated.

09875477-060601

8. The method of claim 7 wherein scrolling an image comprises removing at least one tool bar from the display while scrolling the image.

5 9. The method of claim 7 wherein the control step for using a context value to control the operation of one or more aspects of the device comprises changing the orientation of an image on the display based on a tilt context value unless the tilt
10 context value is being used to control scrolling of an image on the display.

10. The method of claim 1 wherein generating one or more context values comprises generating a
15 holding context value that indicates that the user is holding the device and at least one orientation context value that indicates that the device is in an orientation consistent with the user wanting to use the device and wherein the control step for using a
20 context value to control the operation of one or more aspects of the device comprises placing the device in a full power mode based on the holding context value and the orientation context value.

25 11. The method of claim 1 wherein generating one or more context values comprises generating a holding context value that indicates that the user is holding the device and wherein the control step for using a context value to control the operation of one

09875477-060601

or more aspects of the device comprises preventing the device from entering an idle mode based on the holding context value.

5 12. The method of claim 1 wherein generating one or more context values comprises generating a sequence of proximity context values that indicate the proximity between the device and an object and wherein the control step for using a context value to
10 control the operation of one or more aspects of the device comprises preventing the device from entering an idle mode based on the sequence of proximity context values.

15 13. The method of claim 12 wherein the control step for using a context value to control the operation of one or more aspects of the device comprises allowing the device to enter an idle mode if all of the proximity context values in the
20 sequence of proximity context values are the same.

14. The method of claim 1 wherein generating one or more context values comprises generating a holding context value that indicates that the user is
25 holding the device and at least one orientation context value that indicates that the device is in an orientation consistent with the user wanting to use the device and wherein the control step for using a context value to control the operation of one or more

09875477-060601

aspects of the device comprises activating an application based on the holding context value and the orientation context value.

5 15. The method of claim 14 wherein activating an application comprises activating a sound capturing application so that it captures sound.

10 16. A device with a display, the device comprising:

at least one sensor that generates a sensor signal indicative of the orientation of the device relative to the earth;

15 control means for using the sensor signal to control the operation of at least one aspect of the device.

20 17. The device of claim 16 wherein the at least one sensor comprises a tilt sensor.

25 18. The device of claim 17 wherein the control means uses the sensor signal from the tilt sensor to scroll an image on the display, the scrolling being controlled in part based on the difference between a current signal from the tilt sensor and a signal from the tilt sensor when tilt scrolling is initiated.

09875477-060601

19. The device of claim 18 wherein scrolling further comprises removing at least one tool bar from the display during scrolling.

5 20. The device of claim 17 wherein the control means uses the sensor signal from the tilt sensor to set the orientation of an image on the display.

21. The device of claim 20 wherein the control
10 means does not change the orientation of the image on the display when a portion of the image is being scrolled.

22. The device of claim 20 wherein the device
15 further comprises a directional input and wherein the control means further uses the sensor signal from the tilt sensor to set a mapping between the directional input and a direction relative to an image on the display.

20
23. The device of claim 20 wherein the sensor
signal from the tilt sensor indicates that the device
is positioned so that the display is substantially
parallel to the earth and wherein the control means
25 uses this sensor signal to set the orientation of the
image on the display to a last stable image
orientation.

09875477.060604
T0909072452860

24. The device of claim 17 wherein the control means uses the sensor signal from the tilt sensor to adjust the contrast on the display.

5 25. The device of claim 17 wherein the at least one sensor further comprises a touch sensor.

26. The device of claim 25 wherein the control means uses the sensor signals from the tilt sensor
10 and touch sensor to determine whether to place the device in a full power mode.

27. The device of claim 25 wherein the control means uses the sensor signals from the touch sensor
15 to determine whether to place the device in an idle power mode.

28. The device of claim 25 wherein the control means uses the sensor signals from the tilt sensor
20 and touch sensor to determine whether to activate an application.

29. The device of claim 17 wherein the at least one sensor further comprises a proximity sensor.

25

30. The device of claim 29 wherein the control means uses the sensor signals from the proximity sensor to determine whether to place the device in an idle power mode.

09875477.060601